

WEATHERPRO™ PLUS SHRINK WRAP

Keep moisture, dust, and debris away with WeatherPRO™ Shrink Wrap. Manufactured from premium grade polyethylene film, WeatherPRO™ Shrink Wrap protects your structure from extreme weather, moisture, wind, and more. When heat is applied, the film shrinks tightly over anything it covers. A tightly contoured fit offers a tailored solution for covering, securing, protecting, and packaging the structure.

June 2023		WeatherPRO™ Plus Shrink Wrap		
Material Properties	Rev	ASTM	Flame Retardant	Non-Flame Retardant
	Thickness (Nominal)		9 mil 0.23 mm	12 mil 0.31 mm
	Color		White	White
	Tensile Strength MD	D882		30 psi 207 kPa
	Tensile Strength CD	D882		30 psi 207 kPa
	Tear Strength MD	D1922		3 lb 13 N
	Tear Strength CD	D1922		4.3 lb 19 N
	Tensile Yield	D882	1400 psi/1200 psi	
	Tensile Break	D882	2500 psi / 2400 psi	
	Tensile Elongation	D822	600 psi / 700 psi	
	Dart Impact	D1709	750 g	
	Elmendorf Tear	D1922	1200 g / 1500 g	
	Shrink Temperature	D2732	135° C	
	Size			20' x 100'

Disclaimer: Layfield disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

For up-to-date technical information, be sure to visit us online at www.LayfieldGroup.com