



FROM DRILLING FLUIDS TO HAZARDOUS WASTE CONTAINMENT, WE HAVE YOU COVERED

With its exceptional flexibility and endurance properties, Layfield's Enviro Liner® (EL) brand of geomembranes has been a trusted performer in our portfolio for many years. Available in four unique formulations, this series of geomembranes offers solutions for a wide range of containment applications.

The flagship Enviro Liner® 6000 incorporates the latest ultraviolet/anti-oxidant (UV/AO) stabilization technology, providing a new level of UV resistance and endurance properties. It is designed for long-term exposed applications and has excellent chemical resistance, making it one of the most durable geomembranes on the market.



ENHANCED UV & CHEMICAL RESISTANCE

Offers the latest ultraviolet/anti-oxidant stabilization technology and excellent chemical resistance.



COLD TEMPERATURE HANDLING

Ability to withstand temperatures well below freezing.



EXCELLENT INTERFACE FRICTION PROPERTIES

Available in textured versions on one or both sides, providing superior friction properties.



REDUCED INSTALLATION COSTS

Can be factory fabricated to deliver to the site as large panels, making for an easier installation.



Enviro Liner® Geomembrane Series



► ENVIRO LINER® 1000

A flexible membrane liner developed for the containment of drilling fluids and water used in hydraulic fracturing operations.



► ENVIRO LINER® 4000

A specialized LLDPE polyethylene lining material that combines flexibility, UV stability, and chemical resistance, allowing for easy accommodation to differential settlement. GRI GM 17 compliant.

Layfield's Enviro Liner® geomembrane series can be prefabricated, providing a seamless solution that eliminates the need for on-site seaming and significantly reduces installation time and costs! Our prefabricated Enviro Liner® geomembranes are tailor-made to your specified dimensions, adhering to the industry's highest quality control standards. Meticulously folded and packaged, they ensure a hassle-free installation process.



► ENVIRO LINER® 3000

An economical lining material made from blended/ reprocessed polyethylene resins selected for optimum performance at the lowest cost.



► ENVIRO LINER® 6000

Enviro Liner® 6000 is NSF 61 compliant and fortified with the latest in Ultra Violet/Anti Oxidant (UV/AO) stabilization packages, providing exceptional UV resistance and making it ideal for long-term exposed applications.

> FOR UP-TO-DATE ENVIRO LINER® SPECIFICATIONS, PLEASE SCAN THE QR CODE.



